

# General Contractor Applications

## Replacement of Misplaced Anchors

Pg. 39/46

### C6+/G5 ADHESIVE

- Ideal for hot climates—extended working time formula

Pg. 71

### LDT

Pg. 23

### A7+ ADHESIVE

- Damp holes or underwater
- Dispenses and cures faster in cold weather

Cast-In-Place Bolt in Wrong Location

## Tilt Wall Anchorage

Pg. 79

### BOA COIL

- High shear strength
- Removable
- Reusable

### TRUBOLT

Pg. 63

- Available in 3/4" x 7"
- Drill hole deeper than anchor length, drive into hole after use

Pg. 69

### TRUBOLT +

- 2006 IBC, 2009 IBC, 2012 IBC, & 2015 IBC Compliant
- All seismic zone and cracked concrete approved
- Thru fixture fastening

## Seismic Hold Downs

- Damp holes or underwater
- Fastest cure (35 min. at 60°F)
- Dispenses and cures faster in cold weather

Pg. 23

### A7+ADHESIVE

Pg. 23

### A7+ ADHESIVE

- Damp holes or underwater
- Fastest cure (35 min. at 60°F)
- Dispenses and cures faster in cold weather

## Replacement of Damaged Anchors

Pg. 39

### C6+ ADHESIVE

- NSF Approved
- Vibration resistant
- Corrosion resistant
- Can be used in oversize holes

Pg. 39/46

### C6+/G5 ADHESIVE

- Extended working time—ideal for warm to hot climates
- Can be used in oversize holes

Damaged Cast-In-Place Anchor

For seismic recognition, see ICC-ES evaluation reports.

For installation guidelines for your application, please contact our Technical Services Department at 1-800-848-5611.