

Trubolt+ Wedge Anchor - Technical Data

PART NUMBER	THREAD LENGTH In. (mm)	ANCHOR DIA. & DRILL BIT SIZE (THREADS) PER INCH	OVERALL LENGTH In. (mm)	MAX. THICKNESS OF MATERIAL TO BE FASTENED In. (mm)	QTY/WT PER BOX lbs.	QTY/WT PER MASTER CARTON lbs.
CWS-3830	1-5/8 (41.3)	3/8" - 16	3 (76.2)	5/8 (15.9)	50/ 5.3	400/ 42
CWS-3836	2-3/8 (60.3)	3/8" - 16	3-3/4 (95.3)	1-3/8 (34.9)	50/ 5.9	300/ 35
CWS-3850	3-5/8 (92.1)	3/8" - 16	5 (127.0)	2-5/8 (66.7)	50/ 7.3	250/ 37
CWS-1236	2-1/8 (54.0)	1/2" - 13	3-3/4 (95.3)	3/4 (19.1)	25/ 5.7	150/ 34
CWS-1244	2-7/8 (73.0)	1/2" - 13	4-1/2 (114.3)	1-1/2 (38.1)	25/ 7.0	150/ 40
CWS-1254	3-7/8 (98.4)	1/2" - 13	5-1/2 (139.7)	2-1/2 (63.5)	25/ 8.0	150/ 49
CWS-1270	5-3/8 (136.5)	1/2" - 13	7 (177.8)	4 (101.6)	25/ 9.2	150/ 55
CWS-5850	3-3/16 (81.0)	5/8" - 11	5 (127.0)	1-1/8 (28.6)	10/ 4.7	100/ 48
CWS-5860	4-3/16 (106.4)	5/8" - 11	6 (152.4)	2-1/8 (54.0)	10/ 5.4	50/ 28
CWS-5870	5-3/16 (131.8)	5/8" - 11	7 (177.8)	3-1/8 (79.4)	10/ 6.2	30/ 19
CWS-5884	5-3/4 (146.0)	5/8" - 11	8-1/2 (215.9)	4-5/8 (117.5)	10/ 8.0	30/ 25
CWS-3454	3-5/8 (92.1)	3/4" - 10	5-1/2 (139.7)	1-1/2 (38.1)	50/ 7.6	30/ 38
CWS-3462	4-3/8 (111.1)	3/4" - 10	6-1/4 (158.8)	2-1/4 (57.2)	10/ 8.5	30/ 26
CWS-3470	5-1/8 (130.2)	3/4" - 10	7 (177.8)	3 (76.2)	10/ 9.0	30/ 27
CWS-3484	5-3/4 (146.0)	3/4" - 10	8-1/2 (215.9)	4-1/2 (114.3)	10/ 10.5	30/ 32
CWS-34100	5-3/4 (146.0)	3/4" - 10	10 (254.0)	6 (152.4)	10/ 11.9	30/ 36

Meets ASTM B633 SC1, Type III specifications for electroplating of 5um = .0002" thickness. This coating is well suited for non-corrosive environments.

Trubolt+
Seismic Wedge Anchors
Carbon Steel with Zinc Plating

Strength Design Performance values in accordance with 2015 IBC ITW RED HEAD **TRUBOLT+** and OVERHEAD **TRUBOLT+** EDGE ANCHOR DESIGN INFORMATION TESTED TO ICC-ES AC 193 AND ACI 355.2, IN ACCORDANCE WITH 2015 IBC

TRUBOLT+ AND OVERHEAD **TRUBOLT+** WEDGE INSTALLATION INFORMATION

Parameter	Notation	Units	Nominal Anchor Diameter (inch)											
			3/8		1/2		5/8		3/4					
Anchor outer diameter	d _o	inches	0.361		0.5		0.615		0.7482					
Nominal carbide bit diameter	d _{bit}	inches	3/8		1/2		5/8		3/4					
Effective embedment depth	h _{ef}	inches	1-5/8		2		3-1/4		2-3/4		4-1/4		3-3/4	
Minimum anchor embedment depth	h _{nom}	inches	2		2-1/2		3-3/4		3-1/4		4-3/4		4-3/8	
Minimum hole depth ¹	h _o	inches	2-1/4		2-3/4		4		3-1/2		5		4-5/8	
Minimum concrete member thickness ¹	h _{min}	inches	4		5		4		6		6		8	
Critical edge distance ¹	c _{ac}	ln.	5		3		6		6		7-1/2		6	
Minimum anchor spacing ¹	s _{min}	ln.	3-1/2		2-1/2		6		5-3/4		4		5-3/4	
Minimum edge distance ¹	c _{min}	ln.	3				6		7-1/2		5		7-1/2	
Minimum overall anchor length	l	inches	2-1/2		3-3/4		4-1/2		4-1/4		6		5-1/2	
Installation torque	T _{inst}	ft-lb	30				45		90		110			
Minimum diameter of hole in fastened part	d _h	inches	1/2				5/8		3/4		7/8			

For SI: 1 inch = 25.4 mm, 1 ft-lb = 1.356 N-m.

Trubolt+ Wedge Anchor - Technical Data

Strength Design Performance values in accordance with 2015 IBC

ITW RED HEAD **TRUBOLT+** and OVERHEAD **TRUBOLT+** EDGE ANCHOR DESIGN INFORMATION TESTED TO ICC-ES AC 193 AND ACI 355.2, IN ACCORDANCE WITH 2015 IBC

TRUBOLT+ AND OVERHEAD TRUBOLT+ WEDGE ANCHOR DESIGN INFORMATION¹

Characteristic	Symbol	Units	Nominal Anchor Diameter (inch) ⁴									
			3/8"		1/2"		5/8"		3/4"			
Anchor category	1, 2 or 3	—	1		1		1		1			
Minimum effective embedment depth	h_{ef}	in	1-5/8		2		3-1/4		2-3/4	4-1/4	3-3/4	
Minimum concrete member thickness	h_{min}	in	4	5	4	6	6	8	6	6-1/4	7	8
Critical edge distance	c_{ac}	in	5	3	6	6	7-1/2	6	7-1/2	6-1/2	12	10
Data for Steel Strengths – Tension and Shear												
Minimum specified yield strength	f_y	psi	60,000		55,000		55,000		55,000		55,000	
Minimum specified ultimate strength	f_{uta}	psi	75,000		75,000		75,000		75,000		75,000	
Effective tensile stress area (neck)	A_{se}	in ²	0.056		0.119		0.183		0.266		0.266	
Effective tensile stress area (thread)	A_{se}	in ²	0.075		0.142		0.217		0.332		0.332	
Steel strength in tension	N_{sa}	lbf	4,200		8,925		13,725		19,950		19,950	
Steel strength in shear, uncracked or cracked concrete ⁶	V_{sa}	lbf	1,830		5,175		8,955		14,970		14,970	
Steel strength in shear – seismic loads	V_{eq}	lbf	1,545		5,175		8,955		11,775		11,775	
Strength reduction factor f for tension, steel failure modes ²			0.75		0.75		0.75		0.75		0.75	
Strength reduction factor f for shear, steel failure modes ²			0.60		0.65		0.65		0.65		0.65	
Data for Concrete Breakout Concrete Pryout Strengths in Tension and Shear												
Effectiveness factor – uncracked concrete	k_{uncr}	—	24		24		24		24		24	
Effectiveness factor – cracked concrete	k_{cr}	—	17		17		17		17		17	
Modification factor for cracked and uncracked concrete ³	$\Psi_{c,N}$	—	1.0		1.0		1.0		1.0		1.0	
Coefficient for pryout strength	k_{cp}	—	1.0		1.0	2.0		2.0		2.0		
Load-bearing length of anchor	l_e	in	1.625		2.0		3.25		2.75	4.25	3.75	
Strength reduction factor ϕ for tension, concrete failure modes, Condition B ²			0.65		0.65		0.65		0.65		0.65	
Strength reduction factor ϕ for shear, concrete failure modes, Condition B ²			0.70		0.70		0.70		0.70		0.70	
Data for Pullout Strengths												
Pullout strength, uncracked concrete	$N_{p,uncr}$	lbf	See Footnote ⁵		See Footnote ⁵		6,540		5,430	8,900	See Footnote ⁵	
Pullout strength, cracked concrete	$N_{p,cr}$	lbf	See Footnote ⁵		See Footnote ⁵		See Footnote ⁵		See Footnote ⁵		See Footnote ⁵	
Pullout strength for seismic loads	N_{eq}	lbf	See Footnote ⁵		See Footnote ⁵		See Footnote ⁵		See Footnote ⁵	6,715	See Footnote ⁵	
Strength reduction factor f for tension, pullout failure modes, Condition B ²			See Footnote ⁵		0.65		0.65		0.65		See Footnote ⁵	
Additional Anchor Data												
Axial stiffness in service load range in uncracked concrete	b_{uncr}	lbf/in	100,000		250,000		250,000		250,000		250,000	
Axial stiffness in service load range in cracked concrete	b_{cr}	lbf/in	40,000		20,000		20,000		20,000		20,000	

For SI: 1 inch = 25.4 mm, 1 in² = 645.16mm², 1 lbf = 4.45 N, 1 psi = 0.006895 MPa, 1 lbf • 102/in = 17,500 N/m.

¹ The 1/2", 5/8" and 3/4" diameter Trubolt+ Wedge Anchors are ductile steel elements as defined by ACI 318 D.1. The 3/8" diameter Trubolt+ is considered ductile under tension loading and brittle under shear loading.

² All values of ϕ apply to the load combinations of IBC Section 1605.2, ACI 318 Section 9.2 or UBC Section 1612.2. If the load combinations of Appendix C or UBC Section 1909.2 are used, the appropriate value of ϕ must be determined in accordance with ACI 318 D.4.5. For installations where reinforcement that complies with ACI 318 Appendix D requirements for Condition A is present, the appropriate ϕ factor must be determined in accordance with ACI 318 D.4.4.

³ For all design cases $\Psi_{c,N} = 1.0$. The appropriate effectiveness factor for cracked concrete (k_{cr}) or uncracked concrete (k_{uncr}) must be used.

⁴ The actual diameter for the 3/8" diameter anchor is 0.361" for the 5/8" diameter anchor is 0.615" and the 3/4" diameter anchor is 0.7482".

⁵ Anchor pullout strength does not control anchor design. Determine steel and concrete capacity only.

⁶ Steel strength in shear values are based on test results per ACI 355.2, Section 9.4 and must be used for design.

Trubolt+ Wedge Anchor - Technical Data

Strength Design Performance values in accordance with 2015 IBC

TRUBOLT+ AND OVERHEAD TRUBOLT+ WEDGE ANCHOR ALLOWABLE STRESS DESIGN (ASD) VALUES FOR ILLUSTRATIVE PURPOSES

Anchor Notation	Anchor Embedment Depth	Effective Embedment Depth	Allowable Tension Load
	(inches), h_{nom}	(inches), h_{ef}	(lbs)
3/8	2	1-5/8	1,090
1/2	2-1/2	2	1,490
	3-3/4	3-1/4	2,870
5/8	3-1/4	2-3/4	2,385
	4-3/4	4-1/4	3,910
3/4	4-3/8	3-3/4	3,825

For SI: 1 inch = 25.4 mm, 1 ft-lb = 4.45N.

Design Assumptions:

¹ Single anchor with static shear load only.

² Load combinations from 2006 IBC, Sections 1605.2.1 and 1605.3.1 (no seismic loading).

³ Thirty percent dead load and 70 percent live load, controlling load combination 1.2D + 1.6L

⁴ Calculation of weighted average: 1.2D + 1.6L = 1.2 (0.3) + 1.6 (0.7) = 1.48

⁵ Values do not include edge distance or spacing reductions.

ITW RED HEAD TRUBOLT+ and OVERHEAD TRUBOLT+ WEDGE ANCHOR DESIGN INFORMATION FOR INSTALLATION IN THE SOFFIT OF CONCRETE FILL ON METAL DECK FLOOR AND ROOF ASSEMBLIES

TRUBOLT+ AND OVERHEAD TRUBOLT+ WEDGE ANCHOR DESIGN INFORMATION

Characteristic	Symbol	Units	Nominal Anchor Diameter				
			3/8"	1/2"		5/8"	
			Upper /Lower	Upper /Lower	Lower Only	Lower Only	Lower Only
			$h_{ef} = 1-5/8"$	$h_{ef} = 2"$	$h_{ef} = 3-1/4"$	$h_{ef} = 2-3/4"$	$h_{ef} = 4-1/4"$
Pullout strength, uncracked concrete over metal deck	$N_{p, deck, uncr}$	lbf	2,170	2,515	5,285	3,365	6,005
Pullout strength, cracked concrete over metal deck	$N_{p, deck, cr}$	lbf	1,650	1,780	4,025	2,405	5,025
Reduction factor for pullout strength in tension, Condition B	ϕ	--	0.65				
Shear strength, uncracked concrete over metal deck	$V_{p, deck, uncr}$	lbf	1,640	2,200	3,790	2,890	6,560
Reduction factor for steel strength in shear	ϕ	--	0.60	0.65			
Anchor embedment depth	h_{nom}	in	2.0	2.5	3.75	3.25	4.75

For SI: 1 inch = 25.4 mm, 1 lbf = 4.45 N

Trubolt+ Wedge Anchor - Technical Data

ITW RED HEAD TRUBOLT+ WEDGE ANCHOR DESIGN INFORMATION TESTED TO ICC-ES AC 193 AND ACI 355.2, IN ACCORDANCE WITH 2015 IBC

TRUBOLT+ STAINLESS STEEL WEDGE ANCHOR DESIGN INFORMATION¹

Characteristic	Symbol	Units	1/2"				5/8"	
Anchor category	1, 2 or 3	—	1				1	
Minimum effective embedment depth	h_{ef}	in	2		3-1/4		2-3/4	4-1/4
Minimum concrete member thickness	h_{min}	in	4	6	6	8	6	6-1/4
Critical edge distance	c_{ac}	in	6	6	7-1/2	6	7-1/2	6-1/2
Data for Steel Strengths – Tension and Shear								
Minimum specified yield strength	f_y	psi	65,000				65,000	
Minimum specified ultimate strength	f_{uta}	psi	100,000				100,000	
Effective tensile stress area (neck)	A_{se}	in ²	0.119				0.183	
Effective tensile stress area (thread)	A_{se}	in ²	0.142				0.217	
Steel strength in tension	N_{sa}	lbf	11,900				18,300	
Steel strength in shear, uncracked or cracked concrete ⁵	V_{sa}	lbf	7,265				10,215	
Steel strength in shear – seismic loads	V_{eq}	lbf	5,805				8,105	
Strength reduction factor f for tension, steel failure modes ²			0.75				0.75	
Strength reduction factor f for shear, steel failure modes ²			0.65				0.65	
Data for Concrete Breakout Concrete Pryout Strengths in Tension and Shear								
Effectiveness factor – uncracked concrete	k_{uncr}	—	24				24	
Effectiveness factor – cracked concrete	k_{cr}	—	17				17	
Modification factor for cracked and uncracked concrete ³	$\psi_{c,N}$	—	1.0				1.0	
Coefficient for pryout strength	k_{cp}	—	1.0	2.0			2.0	
Load-bearing length of anchor	l_e	in	2.0		3.25		2.75	4.25
Strength reduction factor f for tension, concrete failure modes, Condition B ²			0.65				0.65	
Strength reduction factor f for shear, concrete failure modes, Condition B ²			0.70				0.70	
Data for Pullout Strengths								
Pullout strength, uncracked concrete	$N_{p,uncr}$	lbf	See Footnote ⁴		6,540		5,430	8,900
Pullout strength, cracked concrete	$N_{p,cr}$	lbf	See Footnote ⁴					
Pullout strength for seismic loads	N_{eq}	lbf	2,345		See Footnote ⁴		See Footnote ⁴	
Strength reduction factor f for tension, pullout failure modes, Condition B ²			0.65				0.65	
Additional Anchor Data								
Axial stiffness in service load range in uncracked concrete	b_{uncr}	lbf/in	250,000				250,000	
Axial stiffness in service load range in cracked concrete	b_{cr}	lbf/in	20,000				20,000	

For SI: 1 inch = 25.4 mm, 1 in² = 645.16mm², 1 lbf = 4.45 N, 1 psi = 0.006895 MPa, 1 lbf • 102/in = 17,500 N/m.

¹ The 1/2" and 5/8" diameter Trubolt+ Wedge Anchors are ductile steel elements as defined by ACI 318 D.1.

² All values of f apply to the load combinations of IBC Section 1605.2, ACI 318 Section 9.2 or UBC Section 1612.2. If the load combinations of Appendix C or UBC Section 1909.2 are used, the appropriate value of f must be determined in accordance with ACI 318 D.4.5. For installations where reinforcement that complies with ACI 318 Appendix D requirements for Condition A is present, the appropriate f factor must be determined in accordance with ACI 318 D.4.4.

³ For all design cases $\psi_{c,N} = 1.0$. The appropriate effectiveness factor for cracked concrete (k_{cr}) or uncracked concrete (k_{uncr}) must be used.

⁴ Anchor pullout strength does not control anchor design. Determine steel and concrete capacity only.

⁵ Steel strength in shear values are based on test results per ACI 355.2, Section 9.4 and must be used for design.

TRUBOLT+ STAINLESS STEEL WEDGE INSTALLATION INFORMATION

Parameter	Notation	Units	1/2"				5/8"	
Anchor outer diameter	d_o	inches	0.5				0.615	
Nominal carbide bit diameter	d_{bit}	inches	1/2				5/8	
Effective embedment depth	h_{ef}	inches	2		3-1/4		2-3/4	4-1/4
Minimum anchor embedment depth	h_{nom}	inches	2-1/2		3-3/4		3-1/4	4-3/4
Minimum hole depth ¹	h_o	inches	2-3/4		4		3-1/2	5
Minimum concrete member thickness ¹	h_{min}	inches	4	6	6	8	6	6-1/4
Critical edge distance ¹	c_{ac}	in.	6	6	7-1/2	6	7-1/2	6-1/2
Minimum anchor spacing ¹	s_{min}	in.	6	5-3/4	4	5-3/4	8	6
Minimum edge distance ¹	c_{min}	in.	6				7-1/2	5
Minimum overall anchor length	l	inches	3-3/4		4-1/2		4-1/4	6
Installation torque	T_{inst}	ft-lb	45				90	
Minimum diameter of hole in fastened part	d_h	inches	5/8				3/4	

For SI: 1 inch = 25.4 mm, 1 ft-lb = 1.356 N-m.