

Drywall Contractor & Carpenter Applications

Window and Door Frames

DYNABOLT

Pg. 85



- Counter sunk and threshold head styles
- Works in concrete, block and brick

TAPCON

Pg. 88



- Works in solid and hollow base material
- Removable
- Can be set flush with Phillips head if counter sunk

Drywall Track

Ceiling Track

Floor Track

Pg. 88

TAPCON



- Simple to use—drill hole and screw in
- Setting tool (C1000) available for tight spaces

Pg. 88

TAPCON



- Counter sunk flathead style for flush installation
- Works in concrete or block
- Available in 3/16" and 1/4" diameters

Furring Strips

- Drill hole, install by hand or impact wrench

LDT

Pg. 71



Framing/Sill Plating

TRUBOLT

Pg. 63

- Full threaded for maximum versatility
- Metro-Dade Approved
- Other approvals on page 66

Pg. 69

TRUBOLT +

- 2006 IBC, 2009 IBC, 2012 IBC, & 2015 IBC Compliant
- All seismic zone and cracked concrete approved
- Thru fixture fastening

Pg. 39/46

C6+/G5 ADHESIVE

- High load capacity
- Corrosion resistant
- NSF Approved
- Used for slower cure projects

Pg. 23

A7+ ADHESIVE

- Fast cure
- Works in damp wet conditions
- Use A7+ with threaded rod for this application

For seismic recognition, see ICC-ES evaluation reports.

For installation guidelines for your application, please contact our Technical Services Department at 1-800-848-5611.